

G25WMI-2A-T4i

The **G25** from Doosan Portable Power is dependable power in a small package. The **G25** features Tier 4 engine technology and Doosan Portable Power's legendary rugged enclosure and running gear, ensuring impressive performance regardless of jobsite conditions. The user-friendly controls, 24-hour run time, and sound attenuation make the **G25** ideal for events, emergency backups, and construction.



Prime Output
25 kVA (20 kW)

Sound Level (100% Load)
66 dB(A)

Specifications

Prime Power Rating

@ 480V-3Ø, 0.8PF, 60Hz	25 kVA (20 kW), 30 Amps
@ 240V-3Ø, 0.8PF, 60Hz	25 kVA (20 kW), 60 Amps
@ 208V-3Ø, 0.8PF, 60Hz	25 kVA (20 kW), 69 Amps
@ 240V-1Ø, 1.0PF, 60Hz 4 Wire / Zig-Zag	20 kVA (20 kW), 28 Amps / 15.6 kVA (15.6 kW), 65 Amps
@ 120V-1Ø, 1.0PF, 60Hz 4 Wire / Zig-Zag	20 kVA (20 kW), 56 Amps / 15.6 kVA (15.6 kW), 65x2 Amps
Voltage Configuration	3-Position Switch
Frequency Capability	60Hz Only

Engine

Engine Make / Model	Mitsubishi S4Q2-Y362
Power Output @ 1800RPM - HP (kWm)	31 (23)

Emissions Tier Level	Tier 4-interim
Fuel Tank Capacity - Gal (L)	36 (136)
Runtime @ 100% Load - Hr	18,9

Dimensions W/ Running Gear

Length - in (mm)	131 (3327)
Width - in (mm)	59.5 (1511)
Height - in (mm)	67 (1702)
Weight (Ready to Run) - lb (kg)	2588 (1174)
Sound Level @ 23 ft (7m) and 100% Load - dB(A)	66

