

I



		DO	GK70B Speci	fications	
	Generator Type				Revolving Field Brushless AC
	Rated Output			kVA	70
				kW	56
	Voltage – Three phase			V	240, 480
Alternator	Voltage – Single phase			V	120,139, 240, 277
	g_		Single phase - 120V		155.5 (4 wire), 168x2(Zig-zag)
	Amps	Single phase - 240V		A	77.8 (4 wire), 168(Zig-zag)
		Three phase - 240V		A	168
		Three phase - 480V		A	84
	Frequency			Hz	60
	Rated speed			rpm	1800
				ipin	3-phase, 4-wire
	Winding				Star with neutral / Zig-zag
	Power factor				.8
	Insulation class				H
	Excitation				Static excitation (brushless)
	No. of poles				4
					Vertical Water-cooled 4cycle Diesel
	Туре				Engine
	Model (Manufacturer)				4BG1T (ISUZU) EPA2
	No. of Cylinders (bore x stroke)			(in./ mm)	4 (4.13 x 4.92 /105 x 125)
	Continuous rated output			hp	82
	Rated speed			rpm	1800
	Displacement			Cu .in./liters	264.2/ 4.329
	Combustion system				Direct Fuel Injection, Turbo Charger
	Cooling method				Radiator
	Lubricating method				Forced lubrication
	Starting method				Electric
	Fuel				Diesel
	Lubricant oil				CD class or higher
	Fuel tank capacity			gal./liters	33/ 125
	Fuel Consumption		Full Load	gal./liters	4.39/ 16.6
			75%	gal./liters	3.33/ 12.6
			50%	gal./liters	2.38/ 9.0
			25%	gal./liters	1.51/ 125
	Lubricant volume			gal./liters	3.8/ 5.7
	Cooling water volume			gal./liters	4.5/ 17
	Starting motor capacity			V-kW	12V, 2.5 kW
	Charging alternator capacity			V-A	12V-60A
	Battery capacity			V-A V-AH	12V-80A
Meters	Voltage/Frequency/Amperage/Hour			v - Al I	12 V-00/ALL
Voltage	vollaye/	пециенсу/Аптрета		+	
Regulation	Automatic Voltage Regulator				
Shutdowns	Oil pressure, Water temperature			1	Lamp indication with shutdown
Warning	Battery charge			1	Lamp indication
Unit	Dimensions (L x W x H)			in./mm	82.3x34.6X48.8/2090x880x1240
	Dry weight			lbs./kg	2745 /1245
Sound Level	No Load				62 dBA (23 feet)

Specifications are subject to change without notice.

Shindaiwa Construction Products 11975 SW Herman Road Tualatin, OR 97062 Voice 503-692-3070 Fax 503-692-6696 www.kwietpower.com